



PIGNONI SEMPLICI TEMPERATI AD INDUZIONE PER CATENE A RULLI - DIN 8187 - ISO 606



SIMPLEX SPROCKETS WITH HARDENED TEETH FOR ROLLER CHAINS - DIN 8187 - ISO 606

3/8" x 7/32"

9,525 x 5,72 mm

Rullo 6,35 mm

06B - 1



B1	C	r3
5,3	1	10

Materiale acciaio C45

Z	de	dp	dm	D1	A	Kg.
13	43,5	39,80	28	8	25	0,13
14	46,5	42,80	31	8	25	0,16
15	49,5	45,81	34	8	25	0,19
16	52,5	48,82	37	10	28	0,24
17	55,5	51,83	40	10	28	0,28
18	58,6	54,85	43	10	28	0,33
19	61,6	57,87	45	10	28	0,36
20	64,6	60,89	46	10	28	0,39
21	67,6	63,91	48	12	28	0,42
22	70,6	66,93	50	12	28	0,46
23	73,7	69,95	52	12	28	0,50
24	76,7	72,97	54	12	28	0,54
25	79,7	76,00	57	12	28	0,60
30	94,8	92,12	60	12	30	0,72



Z	de	dp	dm	D1	A	Kg.

1/2" x 5/16"

12,7 x 7,75 mm

Rullo 8,51 mm

08B - 1



B1	C	r3
7,2	1,3	1,3

Materiale acciaio C45

Z	de	dp	dm	D1	A	Kg.
12	53,9	49,07	33	10	28	0,21
13	57,9	53,06	37	10	28	0,26
14	61,9	57,07	41	10	28	0,32
15	65,9	61,09	45	10	28	0,38
16	69,9	65,10	50	12	28	0,46
17	74,0	69,11	52	12	28	0,51
18	78,0	73,14	56	12	28	0,59
19	82,0	77,16	60	12	28	0,67
20	86,0	81,19	64	12	28	0,76
21	90,1	85,22	68	14	28	0,85
22	94,1	89,24	70	14	28	0,91
23	98,1	93,27	70	14	28	0,94
24	102,1	97,29	70	14	28	0,98
25	106,2	101,33	70	14	28	1,01
30	126,3	121,50	80	16	30	1,46

Z	de	dp	dm	D1	A	Kg.



PIGNONI SEMPLICI TEMPERATI AD INDUZIONE PER CATENE A RULLI - DIN 8187 - ISO 606



SIMPLEX SPROCKETS WITH HARDENED TEETH FOR ROLLER CHAINS - DIN 8187 - ISO 606

5/8" x 3/8"

15,875 x 9,65 mm

Rullo 10,16 mm

10B - 1



B1	C	r3
9,1	1,6	1,6

Materiale acciaio C45

Z	de	dp	dm	D1	A	Kg.
12	68,2	61,34	42	12	30	0,37
13	73,2	66,32	47	12	30	0,46
14	78,2	71,34	52	12	30	0,56
15	83,2	76,36	57	12	30	0,67
16	88,3	81,37	60	12	30	0,76
17	93,3	86,39	60	12	30	0,88
18	98,3	91,42	70	14	30	1,01
19	103,3	96,45	70	14	30	1,15
20	108,4	101,49	75	14	30	1,21
21	113,4	106,52	75	16	30	1,35
22	118,4	111,55	80	16	30	1,41
23	123,5	116,58	80	16	30	1,47
24	128,5	121,62	80	16	30	1,54
25	133,6	126,66	80	16	30	1,60
30	158,8	151,87	90	20	35	2,41



Z	de	dp	dm	D1	A	Kg.

3/4" x 7/16"

19,05 x 11,68 mm

Rullo 12,07 mm

12B - 1



B1	C	r3
11,1	2	19

Materiale acciaio C45

Z	de	dp	dm	D1	A	Kg.
12	81,8	73,60	52	16	35	0,65
13	87,8	79,59	58	16	35	0,80
14	93,8	85,61	64	16	35	0,97
15	99,8	91,63	70	16	35	1,16
16	105,8	97,65	75	16	35	1,34
17	111,9	103,67	80	16	35	1,53
18	117,9	109,71	80	16	35	1,61
19	123,9	115,75	80	16	35	1,70
20	130,0	121,78	80	16	35	1,80
21	136,0	127,82	90	20	40	2,35
22	142,0	133,86	90	20	40	2,46
23	148,1	139,90	90	20	40	2,56
24	154,1	145,94	90	20	40	2,68
25	160,2	152,00	90	20	40	2,80
30	190,4	182,25	95	20	40	3,63

Z	de	dp	dm	D1	A	Kg.



PIGNONI SEMPLICI TEMPERATI AD INDUZIONE PER CATENE A RULLI - DIN 8187 - ISO 606



SIMPLEX SPROCKETS WITH HARDENED TEETH FOR ROLLER CHAINS - DIN 8187 - ISO 606

1" x 17,02 mm

25,4 x 17,02 mm

Rullo 15,88 mm

16B - 1



B1	C	r3
16,2	2,5	26

Materiale acciaio C45

Z	de	dp	dm	D1	A	Kg.
12	109,7	98,14	69	16	40	1,43
13	117,7	106,12	78	16	40	1,77
14	125,7	114,15	84	16	40	2,08
15	133,7	122,17	92	16	40	2,46
16	141,8	130,20	100	20	45	3,14
17	149,8	138,22	100	20	45	3,34
18	157,8	146,28	100	20	45	3,56
19	165,9	154,33	100	20	45	3,78
20	173,9	162,38	100	20	45	4,03
21	182,0	170,43	110	20	50	5,01
22	190,1	178,48	110	20	50	5,28
23	198,1	186,53	110	20	50	5,56
24	206,1	194,59	110	20	50	5,86
25	214,2	202,65	110	20	50	6,16
30	254,6	243,00	120	20	50	8,38

Z	de	dp	dm	D1	A	Kg.

