



PIGNONI PER BUSSOLA CONICA TEMPERATI AD INDUZIONE - DIN 8187 - ISO 606



SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH - DIN 8187 - ISO 606

3/8" x 7/32"

9,525 x 5,72 mm

Rullo 6,35 mm

06B - 1



B1	C	r3
5,3	1	10

Materiale acciaio C45

Z	de	dp	dm	A	semplici bussola	Kg.
17	55,5	51,83	45	22	1008	0,11
19	61,6	57,86	45	22	1008	0,15
21	67,6	63,90	46	22	1008	0,18
23	73,7	69,95	63	25	1210	0,27
25	79,7	75,99	63	25	1210	0,32



Z	de	dp	dm	A	semplici bussola	Kg.
27	85,7	82,04	63	25	1210	0,34
30	94,8	91,12	63	25	1210	0,39

1/2" x 5/16"

12,7 x 7,75 mm

Rullo 8,51 mm

08B - 1



B1	C	r3
7,2	1,3	13

Materiale acciaio C45

Z	de	dp	dm	A	semplici bussola	Kg.
15	66,5	61,80	45	22	1008	0,16
17	74,5	69,11	60	25	1210	0,22
19	82,5	77,15	63	25	1210	0,33
21	90,6	85,21	71	25	1610	0,36
23	98,7	93,26	76	25	1610	0,50



Z	de	dp	dm	A	semplici bussola	Kg.
25	106,7	101,32	76	25	1610	0,56
27	114,8	109,39	76	25	1610	0,63
30	126,9	121,49	90	32	2012	0,91

5/8" x 3/8"

15,875 x 9,65 mm

Rullo 10,16 mm

10B - 1



B1	C	r3
9,1	1,6	16

Materiale acciaio C45

Z	de	dp	dm	A	semplici bussola	Kg.
13	73,2	66,33	47	22	1008	0,23
15	83,2	76,35	60	25	1210	0,30
17	93,3	86,39	71	25	1610	0,38
19	103,3	96,44	75	25	1610	0,54
21	113,4	106,51	76	25	1610	0,65

Z	de	dp	dm	A	semplici bussola	Kg.
23	123,5	116,58	76	25	1610	0,77
25	133,6	126,66	90	32	2012	1,05
27	143,6	136,74	90	32	2012	1,17
30	158,8	151,87	90	32	2012	1,40



PIGNONI PER BUSSOLA CONICA TEMPERATI AD INDUZIONE - DIN 8187 - ISO 606 **SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH - DIN 8187 - ISO 606**


3/4" x 7/16"

19,05 x 11,68 mm
Rullo 12,07 mm
12B - 1

B1	C	r3
11,1	2	19

Materiale acciaio C45

Z	de	dp	dm	A	semplici bussola	Kg.
13	87,8	79,60	60	25	1210	0,35
15	99,8	91,62	70	25	1610	0,44
17	111,9	103,67	76	25	1610	0,66
19	123,9	115,73	90	32	2012	0,94
21	136,0	127,81	102	44	2517	1,24




1" x 17,02 mm

25,4 x 17,02 mm
Rullo 15,88 mm
16B - 1

B1	C	r3
16,2	2,5	26

Materiale acciaio C45

Z	de	dp	dm	A	semplici bussola	Kg.
15	133,7	122,16	76	38	1615	1,30
17	149,8	138,23	90	32	2012	1,59
19	165,9	154,31	108	44	2517	2,29
21	182,0	170,42	110	44	2517	2,81
23	198,1	186,53	110	44	2517	3,38




1"1/4 x 3/4"

31,75 x 19,56 mm
Rullo 19,05 mm
20B - 1

B1	C	r3
18,5	3,5	32

Materiale acciaio C45

Z	de	dp	dm	A	semplici bussola	Kg.
15	167,7	152,72	110	44	2517	3,39
17	187,7	172,78	110	44	2517	5,07
19	207,9	192,91	110	44	2517	6,75
21	228,0	213,04	120	44	2517	7,70
23	248,2	233,17	120	44	2517	8,78



Z	de	dp	dm	A	semplici bussola	Kg.
25	268,4	253,33	120	44	2517	9,50