





CORONE PER CATENE A RULLI - DIN 8188 - ISO 606 - ANSI B 29.1

PLATE WHEELS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 40

12,7 x 7,95 mm
Rullo 7,95 mm
08A - 1



B1	B2	B3	b1	C	r3
7,2				1,6	13,5

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
8	39,3	33,18						
9	43,2	37,13						
10	47,2	41,10	8	0,06				
11	51,2	45,07						
12	55,2	49,07						
13	59,2	53,06	10	0,10				
14	63,2	57,07						
15	67,2	61,09						
16	71,2	65,10						
17	75,2	69,11	10	0,18				
18	79,2	73,14						
19	83,3	77,16	10	0,23				
20	87,3	81,19	10	0,27				
21	91,3	85,22	12	0,28				
22	95,4	89,24						
23	99,4	93,27						
24	103,4	97,29	12	0,38				
25	107,4	101,33						
26	111,5	105,36						
27	115,5	109,40						
28	119,5	113,42						
29	123,6	117,46						
30	127,6	121,50	16	0,58				
31	131,6	125,54						
32	135,7	129,56	16	0,68				
33	139,7	133,60						
34	143,8	137,64	16	0,78				
35	147,8	141,68	16	0,83				
36	151,8	145,72						
37	155,9	149,76						
38	159,9	153,80	16	0,98				
39	163,9	157,83						
40	168,0	161,87						
41	172,5	165,91						
42	176,6	169,95						
43	180,6	173,99						
44	184,6	178,03	20	1,32				
45	188,7	182,07						
46	192,7	186,10						
47	196,8	190,14						
48	200,8	194,18	20	1,58				
49	204,8	198,22						
50	208,9	202,26	20	1,73				

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
51	212,9	206,30						
52	217,0	210,34						
53	221,0	214,37						
54	225,0	218,43						
55	229,1	222,46						
56	233,1	226,50						
57	237,2	230,54	20	2,25				
58	241,2	234,62						
59	245,2	238,62						
60	249,3	242,66						
62	257,4	250,74						
64	265,4	258,82						
65	269,5	262,86						
66	273,5	266,90						
68	281,6	274,99						
70	289,7	283,07						
72	297,8	291,16						
75	309,9	303,27						
76	313,9	307,33						
78	322,0	315,40						
80	330,1	323,48						
85	350,3	343,69						
90	370,5	363,90						
95	390,7	384,11						
100	410,9	404,31						
110	451,4	444,74						
114	467,5	460,90						
120	491,8	485,16						
125	512,0	505,37						



CORONE PER CATENE A RULLI - DIN 8188 - ISO 606 - ANSI B 29.1



PLATE WHEELS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 50

15,875 x 9,53 mm

Rullo 10,16 mm

10A - 1



B1	B2	B3	b1	C	r3
8,7				2	17

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
8	48,4	41,48	10	0,06				
9	53,3	46,42	10	0,09				
10	58,3	51,37	10	0,11				
11	63,2	56,34	10	0,14				
12	68,2	61,34	10	0,17				
13	73,2	66,32	10	0,20				
14	78,2	71,34	12	0,23				
15	83,2	76,36	12	0,27				
16	88,3	81,37	12	0,31				
17	93,3	86,39	12	0,36				
18	98,3	91,42	12	0,41				
19	103,3	96,45	12	0,46				
20	108,4	101,49	12	0,51				
21	113,4	106,52	12	0,57				
22	118,4	111,55	12	0,62				
23	123,5	116,58	12	0,68				
24	128,5	121,62	12	0,75				
25	133,6	126,66	12	0,82				
26	138,6	131,70	16	0,88				
27	143,6	136,75	16	0,95				
28	148,7	141,78	16	1,03				
29	153,7	146,83	16	1,11				
30	158,8	151,87	16	1,19				
31	163,8	156,92	16	1,28				
32	168,9	161,95	16	1,36				
33	173,9	167,00	16	1,45				
34	178,9	172,05	16	1,55				
35	184,0	177,10	16	1,64				
36	189,0	182,15	20	1,73				
37	194,1	187,20	20	1,83				
38	199,1	192,24	20	1,94				
39	204,2	197,29	20	2,05				
40	209,2	202,34	20	2,16				
41	215,8	207,39	20	2,28				
42	220,8	212,44	20	2,39				
43	225,9	217,49	20	2,50				
44	230,9	222,53	20	2,63				
45	236,0	227,58	20	2,75				
46	241,0	232,63	20	2,88				
47	246,1	237,68	20	3,00				
48	251,1	242,73	20	3,14				
49	256,2	247,78	20	3,28				
50	261,2	252,82	20	3,42				

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
51	266,3	257,87	20	3,56				
52	271,3	262,92	20	3,70				
53	276,4	267,97	20	3,85				
54	281,4	273,03	20	4,00				
55	286,5	278,08	20	4,15				
56	291,5	283,13	25	4,30				
57	296,6	288,18	25	4,46				
58	301,6	293,23	25	4,62				
59	306,7	298,27						
60	311,7	303,32	25	4,95				
62	321,8	313,43	25	5,30				
64	331,9	323,53	25	5,65				
65	337,0	328,58	25	5,83				
68	352,1	343,74	25	6,40				
70	362,2	353,84	25	6,79				
72	372,3	363,95	25	7,19				
75	387,5	379,09	25	7,81				
76	392,5	384,16	25	8,02				
78	402,6	394,25	25	8,46				
80	412,7	404,35	25	8,91				
85	438,0	429,62	30	10,06				
90	463,3	454,88	30	11,30				
95	488,5	480,14	30	12,61				
100	513,8	505,40	30	13,99				
110	564,3	555,92	30	16,97				
114	584,5	576,13	30	19,98				
120	614,8	606,44	30	22,17				
125	640,1	631,71	30	24,08				





CORONE PER CATENE A RULLI - DIN 8188 - ISO 606 - ANSI B 29.1

PLATE WHEELS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 60

19,05 x 12,7 mm
Rullo 11,91 mm
12A - 1



B1	B2	B3	b1	C	r3
11,6				2,4	20

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
8	58,1	49,78						
9	64,0	55,70						
10	70,0	61,64						
11	76,0	67,61						
12	81,9	73,60						
13	87,9	79,59	14	0,35				
14	94,0	85,61	14	0,41				
15	100,0	91,63	14	0,48				
16	106,0	97,65	14	0,55				
17	112,0	103,67	14	0,63				
18	118,0	109,71	14	0,71				
19	124,1	115,75						
20	130,1	121,78	14	0,92				
21	136,2	127,82	16	0,99				
22	142,2	133,86	16	1,09				
23	148,2	139,90	16	1,20				
24	154,3	145,94						
25	160,3	152,00	16	1,43				
26	166,4	158,04	16	1,56				
27	172,4	164,09	16	1,68				
28	178,5	170,13	16	1,82				
29	184,5	176,19	16	1,96				
30	190,6	182,25	16	2,10				
31	196,6	188,31	20	2,24				
32	202,7	194,35	20	2,39				
33	208,8	200,40						
34	214,8	206,46	20	2,71				
35	220,9	212,52	20	2,88				
36	226,9	218,58	20	3,06				
37	233,0	224,64						
38	239,0	230,69	20	3,42				
39	245,1	236,75						
40	251,1	242,81	20	3,85				
41	259,1	248,87						
42	265,2	254,93	25	4,19				
43	271,2	260,98						
44	277,3	267,03						
45	283,3	273,10						
46	289,4	279,16						
47	295,5	285,21						
48	301,5	291,27						
49	307,6	297,33						
50	313,6	303,39						

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
51	319,7	309,45						
52	325,8	315,50						
53	331,8	321,56						
54	337,9	327,64						
55	343,9	333,70						
56	350,0	339,75						
57	356,1	345,81						
58	362,1	351,87						
59	368,2	357,93						
60	374,2	363,99						
62	386,4	376,12						
64	398,5	388,24						
65	404,5	394,29						
66	410,6	400,35						
68	422,7	412,49						
70	434,9	424,60						
72	447,0	436,74						
75	465,2	454,91						
76	471,2	460,99						
78	483,3	473,10						
80	495,5	485,22						
85	525,8	515,55						
90	556,1	545,86						
95	586,4	576,17						
100	616,7	606,47						
110	677,4	667,11						
114	701,6	691,36						
120	738,0	727,74						
125	768,3	758,05						





CORONE PER CATENE A RULLI - DIN 8188 - ISO 606 - ANSI B 29.1

PLATE WHEELS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 80

25,4 x 15,88 mm
Rullo 15,88 mm
16A - 1



B1	B2	B3	b1	C	r3
14,6				3,2	27

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
8	77,9	66,37						
9	85,8	74,27						
10	93,8	82,19						
11	101,7	90,14						
12	109,7	98,14	16	0,77				
13	117,7	106,12						
14	125,7	114,15	16	1,01				
15	133,7	122,17						
16	141,8	130,20	20	1,43				
17	149,8	138,22	20	1,64				
18	157,8	146,28	20	1,85				
19	165,9	154,33	20	2,08				
20	173,9	162,38	20	2,12				
21	182,0	170,43	20	2,45				
22	190,1	178,48	20	2,84				
23	198,1	186,53	20	3,13				
24	206,2	194,59	20	3,42				
25	214,2	202,66						
26	222,3	210,72	20	4,05				
27	230,4	218,79						
28	238,4	226,85	20	4,73				
29	246,5	234,92	20	5,09				
30	254,6	243,00	20	5,46				
31	262,6	251,08						
32	270,7	259,13						
33	278,8	267,21	25	6,63				
34	286,9	275,28	25	7,06				
35	294,9	283,36	25	7,49				
36	303,0	291,44						
37	311,1	299,51						
38	319,2	307,59	25	8,88				
39	327,2	315,67						
40	335,3	323,73						
41	345,6	331,82						
42	353,7	339,90						
43	361,7	347,98						
44	369,8	356,06						
45	377,9	364,12						
46	386,0	372,21						
47	394,1	380,29						
48	402,1	388,36						
49	410,2	396,44						
50	418,3	404,52						

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
51	426,5	412,60						
52	434,5	420,67						
53	442,5	428,75						
54	450,6	436,85						
55	458,7	444,93						
56	466,8	453,01						
57	474,9	461,07						
58	482,9	469,16						
59	491,0	477,24						
60	499,1	485,32						
62	515,3	501,50						
64	531,4	517,65						
65	539,5	525,73						
66	547,6	533,80						
68	563,8	549,98						
70	579,9	566,14						
72	596,1	582,32						
75	620,3	606,35						
76	628,4	614,65						
78	644,6	630,80						
80	660,7	646,96						
85	701,2	687,40						
90	741,6	727,81						
95	782,0	768,22						
100	822,4	808,63						
110	903,3	889,48						
114	935,6	921,81						
120	984,1	970,33						
125	1024,5	1010,73						



CORONE PER CATENE A RULLI - DIN 8188 - ISO 606 - ANSI B 29.1



PLATE WHEELS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 100

31,75 x 19,05 mm

Rullo 19,05 mm

20A - 1



B1	B2	B3	b1	C	r3
17,6				4	33,5

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
8	96,0	82,96						
9	106,5	92,84						
10	117,0	102,74						
11	127,0	112,68						
12	137,0	122,68						
13	147,5	132,65						
14	157,6	142,68						
15	167,7	152,72						
16	177,7	162,75						
17	187,7	172,78	20	2,96				
18	197,8	182,85	20	3,28				
19	207,9	192,91						
20	217,9	202,98						
21	228,0	213,04	25	4,62				
22	238,1	223,11						
23	248,2	233,17						
24	258,3	243,23						
25	268,4	253,33						
26	278,4	263,40						
27	288,5	273,48						
28	298,5	283,56						
29	308,6	293,65						
30	318,7	303,75						
31	328,8	313,85						
32	338,9	323,91						
33	349,0	334,01						
34	359,1	344,10						
35	369,2	354,20						
36	379,2	364,30						
37	389,3	374,39						
38	399,4	384,49						
39	409,5	394,59						
40	419,6	404,66						
41	430,7	414,78						
42	440,8	424,88						
43	450,9	434,97						
44	461,0	445,07						
45	471,1	455,17						
46	481,2	465,26						
47	491,3	475,36						
48	501,4	485,46						
49	511,5	495,55						
50	521,6	505,65						

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
51	531,7	515,75						
52	541,8	525,84						
53	551,9	535,94						
54	562,0	546,07						
55	572,1	556,16						
56	582,2	566,26						
57	592,3	576,36						
58	602,4	586,45						
59	612,5	596,55						
60	622,6	606,65						
62	642,8	626,87						
64	663,0	647,06						
65	673,1	657,16						
66	683,2	667,26						
68	703,4	687,48						
70	723,6	707,67						
72	743,8	727,90						
75	774,2	758,19						
76	784,3	768,32						
80	824,7	808,72						
85	875,2	859,25						
90	925,7	909,76						
95	976,2	960,28						
100	1026,7	1010,79						
114	1168,2	1152,26						



CORONE PER CATENE A RULLI - DIN 8188 - ISO 606 - ANSI B 29.1



PLATE WHEELS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 120

38,1 x 25,4 mm

Rullo 22,23 mm

24A - 1



B1	B2	B3	b1	C	r3
23,5				4,8	40,5

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
8	113,0	99,55						
9	125,0	111,40	20	1,47				
10	137,0	123,29	20	1,85				
11	149,0	135,21	25	2,24				
12	161,0	147,22						
13	173,0	159,18	25	3,22				
14	185,0	171,22	25	3,68				
15	197,0	183,26	25	4,34				
16	209,0	195,30	25	4,88				
17	221,0	207,34	25	5,69				
18	233,0	219,42	25	6,29				
19	245,5	231,49						
20	257,5	243,57	25	7,95				
21	270,5	255,65						
22	282,5	267,73						
23	294,5	279,80						
24	307,0	291,88						
25	319,0	304,00	30	12,25				
26	331,0	316,08						
27	343,0	328,19						
28	355,0	340,27						
29	367,5	352,38						
30	379,5	364,50						
31	391,5	376,62						
32	403,5	388,69						
33	415,5	400,81						
34	428,5	412,93						
35	440,0	425,04	30	24,65				
36	452,0	437,16						
37	464,0	449,27						
38	476,5	461,39						
39	488,5	473,50						
40	501,5	485,62						
41	513,5	497,74						
42	525,5	509,85						
43	538,0	521,97						
44	550,0	534,08						
45	562,0	546,20						
46	574,0	558,32						
47	586,5	570,43						
48	598,5	582,55						
49	610,5	594,66						
50	622,5	606,78						

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
51	635,0	618,89						
52	647,0	631,01						
53	659,0	643,13						
54	671,0	655,25						
55	683,5	667,40						
56	695,5	679,50						
57	707,5	691,63						
58	719,5	703,74						
59	731,5	715,86						
60	745,0	727,97						
62	769,0	752,24						
64	793,5	776,48						
65	805,5	788,59						
66	817,5	800,71						
68	842,0	824,98						
70	866,0	849,21						
72	890,5	873,48						
75	926,5	909,83						
76	939,0	921,98						
80	987,5	970,44						
85	1048,0	1031,10						
90	1169,0	1152,33						





CORONE PER CATENE A RULLI - DIN 8188 - ISO 606 - ANSI B 29.1

PLATE WHEELS FOR ROLLER CHAINS - DIN 8188 - ISO 606 - ANSI B 29.1

ASA 140

44,45 x 25,4 mm
Rullo 25,4 mm
28A - 1



B1	B2	B3	b1	C	r3
23,5				5,8	47,5

Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.	Z	de	dp	semplici D1	Kg.	doppie D2	Kg.	triple D3	Kg.
8	132,0	116,15															
9	146,0	129,96	20	2,07													
10	160,0	143,85	20	2,59													
11	174,0	157,77	25	3,04													
12	188,0	171,74	25	3,72													
13	204,0	185,75	25	4,37													
14	218,0	199,76	25	5,16													
15	232,0	213,79															
16	246,0	227,84	30	6,85													
17	260,0	241,90	30	7,68													
18	274,0	255,98															
19	289,0	270,06															
20	303,0	284,15															
21	317,0	298,24															
22	331,0	312,34															
23	345,0	326,44															
24	359,0	340,55															
25	373,0	354,66															
26	387,0	368,77															
27	401,0	382,88															
28	416,0	397,00															
29	430,0	411,12															
30	444,0	425,24															
31	458,0	439,37															
32	472,0	453,49															
33	486,0	467,62															
34	500,0	481,75															
35	514,0	495,88															
36	529,0	510,01															
37	543,0	524,13															
38	557,0	538,27															
39	571,0	552,40															
40	585,0	566,54															
45	656,0	637,22															
50	726,0	707,91															
57	825,0	806,90															
60	869,0	849,32															
76	1095,0	1075,62															